

Calculate Linux - Feature # 206: Target "ALL" for operation with users

D_iN̄,D°N̄,NfN•:	Closed	DYÑ€D, D¾Ñ€D, Ñ,DµÑÑNormal
D•D²Ñ,D¾Ñ€:	Dmitry Fomenko	DšD°Ñ,DµD³D¾Ñ€D, Ñ•Calculate Utilities
D_iD¾D•D°D½:	30.12.2010	D•D°D•D½D°Ñ†DµD½D°:
DžD±D¹¾D²D»DµD½D¾01.2011		D”D°Ñ,D° D²Ñ(D¿D¾D»D¹¾DµD½D, Ñ•:
DcDµD¼D°:	Target "ALL" for operation with users	
DžD¿D, Ñ•D°D½D, Dµ:	Request subj. There is a often necessary to add the user to all (active and configured) services. Now i need add the user in services separately. The same situation with delete tje user from all services. Can you add target ALL to parameters cl-userdel and cl-useradd utility. Thank you.	

$$\mathfrak{D} \sim \tilde{\mathbf{N}} \bullet \tilde{\mathbf{N}}, \mathfrak{D}^{3/4} \tilde{\mathbf{N}} \in \mathfrak{D}_\bullet \tilde{\mathbf{N}} \bullet$$

ÐŸÑ., 14 Ñ•Ð½Ð². 2011, 03:46:36 +0300 - Alexander Tratsevskiy

- $\mathcal{D}\check{Y}\mathcal{D}^\circ\tilde{N}\in\mathcal{D}^\circ\mathcal{D}\frac{1}{4}\mathcal{D}\mu\tilde{N},\tilde{N}\in\mathcal{D}_j\tilde{N},\mathcal{D}^\circ\tilde{N},\tilde{N}f\tilde{N}\bullet\mathcal{D},\mathcal{D}\cdot\mathcal{D}\frac{1}{4}\mathcal{D}\mu\mathcal{D}\frac{1}{2}\mathcal{D},\mathcal{D}\gg\tilde{N}\bullet\tilde{N}\bullet\tilde{N}$ New $\mathcal{D}\frac{1}{2}\mathcal{D}^\circ$ Closed

Instead of `cl-useradd` command with the name of the service will use separate commands packages `calculate-samba`, `calculate-ftp`, etc. Common configuration commands for all services in the Calculate Utilities 2.2 will not.