

Calculate Linux - Bug # 930: Custom overlay (not layman) not syncing with ci-update

Status:	Closed	Priority:	Normal
Author:	Adrien Duck	Category:	
Created:	12/07/2016	Assignee:	
Updated:	08/02/2017	Due date:	
Subject:	Custom overlay (not layman) not syncing with ci-update		

Description: Hi team calculate !

I have a remote (custom) repo, installed on CL.
When i do ci-update, it's not updated.

```
<pre>
12 [20:21:43] root@superlinux: ~ # LANG=C ci-update
Repositories synchronization
* Syncing the Distros repository ... [ ok ]
* Syncing the Calculate repository ... [ ok ]
* Syncing the Gentoo repository ... [ ok ]
* Synchronization finished
System configuration
* Fixing the settings ... [ ok ]
* Updating configuration files ... [ ok ]
* Update server http://10.21.21.253/testing
Checking for updates
* Calculating dependencies ...
* The system is up to date
Rebuilding dependent modules
* Updating configuration files ... [ ok ]
* System update finished!

</pre>
```

But, if I do manually `*emerge --sync*`, it's OKAY.

```
<pre>
13 [20:24:22] root@superlinux: ~ # emerge --sync
>>> Syncing repository 'gentoo' into '/usr/portage'...
/usr/bin/git pull
Already up-to-date.
=== Sync completed for gentoo
>>> Syncing repository 'adrien-overlay' into '/usr/local/portage/adrien-overlay'...
/usr/bin/git pull
remote: Counting objects: 5, done.
remote: Compressing objects: 100% (2/2), done.
remote: Total 5 (delta 1), reused 5 (delta 1), pack-reused 0
Unpacking objects: 100% (5/5), done.
From https://github.com/aaaaadrien/adrien-overlay
 c2625e7..ac83652 master -> origin/master
Updating c2625e7..ac83652
Fast-forward
 virtual/adrien/adrien-1.0.0.ebuild | 25 ++++++
 1 file changed, 25 insertions(+)
create mode 100644 virtual/adrien/adrien-1.0.0.ebuild
```

=== Sync completed for adrien-overlay

* IMPORTANT: 3 news items need reading for repository 'gentoo'.

* Use `eselect news read` to view new items.

</pre>

Custom repo is in `repos.conf`.

Are there a bug ?

History

12/08/2016 12:01 pm - Mikhail Hiretsky

Try to run `@cl-update@` with option "`@-o@`".

12/08/2016 01:07 pm - Adrien Duck

Mikhail Hiretsky wrote:

> Try to run `@cl-update@` with option "`@-o@`".

It doesn't work.

I did `@cl-update -o@` and no updates. If I search a package updated recently (in the overlay), `eix` and `emerge --search` don't show the newest package.

12/08/2016 01:17 pm - Adrien Duck

Just an information.

With this same overlay, installed with same commands, on a official Gentoo, `*eix-sync*` synchronise newest packages.

But I saw that `*eix-sync*` redirect to `*cl-core*` command.

12/09/2016 04:57 pm - Mikhail Hiretsky

Did `@adrien-overlay@` install by layman or another method?

12/09/2016 05:02 pm - Adrien Duck

`adrien-overlay` installed with `repos.conf`

<pre>

```
curl https://raw.githubusercontent.com/aaaadrien/adrien-overlay/master/repos.conf -o /etc/portage/repos.conf/adrien-overlay.conf
```

</pre>

12/11/2016 05:43 pm - Adrien Daugabel

Adrien Daugabel wrote:

> `adrien-overlay` installed with `repos.conf`

>

> [...]

`/etc/calculate/calculate.env`

<pre>

```
# update other overlays
```

```
cl_update_other_set = on
```

</pre>

12/11/2016 11:28 pm - Adrien Duck wrote:

Adrien Daugabel wrote:

```
> adrien-overlay installed with repos.conf
>
> [...]
```

```
<pre>
curl https://raw.githubusercontent.com/aaaaadrien/adrien-overlay/master/repositories.xml -o /etc/layman/overlays/adrien-overlay.xml
rm /etc/portage/repos.conf/adrien-overlay.conf
layman -S
layman -a adrien-overlay
cl-update -veo1
</pre>
```

important:

file name in /etc/layman/overlays/ must match of repo name in repositories.xml

12/11/2016 11:43 pm - Adrien Duck

Adrien Duck wrote:

```
> Adrien Daugabel wrote:
> > adrien-overlay installed with repos.conf
> >
> > [...]
```

I do that, but doesn't work.

12/13/2016 12:30 am - Adrien Duck

Adrien Duck wrote:

```
> Adrien Daugabel wrote:
> > adrien-overlay installed with repos.conf
> >
> > [...]
```

> important:

> file name in /etc/layman/overlays/ must match of repo name in repositories.xml

I tried to install this (my) overlay with Layman. it's OK, but, if I do a new update, cl-update no see it !

12/13/2016 09:44 am - Mikhail Hiretsky

Now @cl-update@ supports layman overlays only.

12/13/2016 09:53 am - Adrien Duck

Now, with cl-utilities 3.5 , cl-update -o works !

why it's not a default value ?

12/13/2016 10:16 am - Mikhail Hiretsky

Does synchronize @cl-update@ without option @-o@, but with value in @calculate.env@?

```
<pre>
cl_update_other_set = on
</pre>
```

12/13/2016 10:53 am - Adrien Duck

Mikhail Hiretsky wrote:

> Does synchronize @cl-update@ without option @-o@, but with value in @calculate.env@?

> [...]

@cl-update@ without option @-o@, but with value in @calculate.env@ : it works.

When I added a "real" Layman overlay (available in @layman -L@ list, it was worked.

12/13/2016 02:07 pm - Adrien Duck

Adrien Daugabel wrote:

> @cl-update@ without option @-o@, but with value in @calculate.env@ : it works.

>

> When I added a "real" Layman overlay (available in @layman -L@ list, it was worked.

OK, seems calculate utils just needed update...

12/23/2016 09:12 pm - Adrien Duck

cl-update -o work.

06/19/2017 01:11 pm - Adrien Duck

Today it doesn't work :(

06/19/2017 01:17 pm - Mikhail Hiretsky

What does command display?

```
<pre>
cl-core-variables-show --filter other
</pre>
```

06/20/2017 11:10 am - Adrien Duck

<pre> * Liste des variables

| Variable | Mode | Localisation | Valeur |
|-----------------------------------|------|--------------------------|--------------------------|
| install.cl_install_other_set | wb | | off |
| builder.cl_builder_other_rep_data | rt | | |
| builder.cl_builder_other_rep_name | rl | | |
| builder.cl_builder_other_rep_path | rl | | |
| update.cl_update_other_rep_data | rt | | adrien-overlay:/var/lib/ |
| | | layman/adrien-overlay,vm | |
| | | ware:/var/lib/layman/vmw | |
| | | are | |
| update.cl_update_other_rep_name | rl | | adrien-overlay,vmware |
| update.cl_update_other_rep_path | rl | | /var/lib/layman/adrien-o |


```

* Updating the eix cache for Vmware, Adrien-overlay, Distros, Calculate, Gentoo * . [ ok ]
* Updating the cache of configurable packages ... [ ok ]
* Suppression des sources et des binaires obsolètes ... [ ok ]
* Update packages index ... [ ok ]
* Synchronisation terminée
Configuration système
* Correction des paramètres ... [ ok ]
* Mise à jour des fichiers de configuration ... [ ok ]
* Update server http://miroir.linuxtricks.fr/testing
Mise à jour des paquets
* Calcul des dépendances ...
* Le système est à jour
* (1 sur 1)
* Compilation de ... [ ok ]
* Installation de ... [ ok ]
Suppression des paquets devenus inutiles
* Calcul des dépendances ... [ ok ]
Recompilation des modules dépendants
* Mise à jour des bibliothèques réservées ... [ ok ]
* Mise à jour des fichiers de configuration ... [ ok ]
* Votre système a bien été mis à jour !

</pre>

```

Is it possible to :

- Add packages name for foreign packages ?
- Add an option in calculate-utilities to always update other overlays when we run ci-update ? (as --stable=off for the first update)

07/16/2017 11:11 am - Adrien Duck

Hi,

- Add packages name for foreign packages => Solved

```

<pre>
ci-update -o
Synchronisation des dépôts
* Checking Distros updates ... [ ok ]
* Checking Calculate updates ... [ ok ]
* Checking Gentoo updates ... [ ok ]
* Synchronisation du dépôt Adrien-overlay ... [ ok ]
* Synchronisation du dépôt Vmware ... [ ok ]
* Actualisation du cache du dépôt Distros ... [ ok ]
* Actualisation du cache du dépôt Calculate ... [ ok ]
* Actualisation du cache du dépôt Adrien-overlay ... [ ok ]
* Actualisation du cache du dépôt Vmware ... [ ok ]
* Updating the eix cache for Vmware, Adrien-overlay, Distros, Calculate, Gentoo ... [ ok ]
* Updating the cache of configurable packages ... [ ok ]
* Suppression des sources et des binaires obsolètes ... [ ok ]
* Update packages index ... [ ok ]
* Synchronisation terminée
Configuration système
* Correction des paramètres ...
* Mise à jour des fichiers de configuration ... [ ok ]
* Update server http://miroir.linuxtricks.fr/testing
Mise à jour des paquets

```

```
* Calcul des dépendances ...
* Liste des paquets à installer
* Nous allons vous faire adorer la tele ! (U) media-video/molotov-1.5.1-r3 (0 KiB)
* 1 paquets à installer, 0 KiB à télécharger
```

Voulez-vous installer ces paquets ? (Yes/No): y

```
* (1 sur 1) Nous allons vous faire adorer la tele !
```

```
* Compilation de media-video/molotov-1.5.1-r3 ...
```

[ok]

```
* Installation de media-video/molotov-1.5.1-r3 [1.5.1-r1] ...
```

```
</pre>
```

But, Add an option in calculate-utilities to always update other overlays when we run cl-update ? (as --stable=off for the first update) => added ?
Please, can you write here when it's ok ?

07/19/2017 01:00 pm - Adrien Duck

```
I ran *cl-core-variables --set update.cl_update_other_set=on*
```

and all is okay.

It's OK for new CL installations.

You can close

08/02/2017 03:02 pm - Alexander Tratsevskiy

- *Status changed from New to Closed*

Files

| | | | |
|------------------------------------|----------|------------|-------------|
| Capture_du_2017-06-20_20-57-17.png | 489.5 KB | 06/20/2017 | Adrien Duck |
|------------------------------------|----------|------------|-------------|